

#6
\$5/mark up**~~Cable terminal or joining means~~**

~~—— The invention relates to a cable terminal or joining means for end face connection of the conductors of a preferably multicore cable, with one plug part which is provided with contact elements, with a core holding and guiding part and with a cable receiver, the core holding and guiding part having core guidance channels and the plug part and the cable receiver can be connected to one another, especially screwed to one another, and in the assembled state the core holding and guiding part being located between the plug part and the cable receiver and being surrounded by the plug part and the cable receiver.~~

~~—— First of all, it will be explained below which of the terms used in the following description, first of the prior art, and then of the invention, have or are to have what meaning.~~

~~—— a) The term "cable" means an electrical line which has at least one core, but generally several cores; if there are several cores, it is a multicore cable. For only one core it is a single core cable.~~

~~—— b) The cores of a cable consist of a conductor and core insulation.~~

~~—— c) In one cable the inherently insulated conductors, therefore the conductors provided with core insulation, in their totality are surrounded by other insulation, the cable insulation. For a single core cable there is no other insulation besides the core insulation.~~

~~—— It was stated at the beginning that the invention relates to a cable terminal or joining means for end face connection of the conductors of a multicore cable. Here the cable can be connected to an electrical device or can be joined in an electrically conductive manner to a second cable. If the cable is connected to an electrical device, it is a terminal means. If two cables are to be connected to one another, it is a joining means. Regardless of whether it is a terminal or a joint, the cable or conductor is always connected by a contact element. Mainly a terminal means is emphasized below. But a joining means in the aforementioned sense is~~

also always intended.

—— In a terminal means for electrically conductive connection of a cable to an electrical device, the electrical device should be understood quite in general; in particular the expression "electrical device" also includes electrical and electronic components, means and devices.

—— It was stated initially that the cable terminal or joining means is intended for end face connection of the conductors of a multicore cable. First of all, it is conventional in practice for multicore cables to be connected, but basically the cable terminal or joining

means CABLE TERMINAL

Background of the Invention

Field of the Invention

—— The present invention relates to cable terminals for end-face connection of the conductors of a multicore cable, the cable terminal having a plug part and a cable receiver that can be connected to one another, especially screwed to one another. In particular, the present invention relates to such cable terminals where the plug part is provided with contact elements and a core holding and guiding part with guidance channels where in the assembled state, the core holding and guiding part is located between the plug part and the cable receiver.

Description of Related Art

—— Initially, it will be explained below the meaning of the terms used herein below both with respect to the prior art and the present invention as well.

- a) The term "cable" means an electrical line which has at least one core, but generally several cores. If there are several cores, it is a multicore cable. For cables with only one core, it is a single-core cable.

b) The cores of a cable includes a conductor and core insulation.

c) In one cable, the conductors are provided with core insulation which insulate the conductors. If there are several cores, the several cores, in their totality, are surrounded by other insulation such as the cable insulation. For a single-core cable, there is no other insulation besides the core insulation.

It was stated above, the invention relates to a cable terminal or joining device for end-face connection of the conductors of a multicore cable. Here, the cable can be connected to an electrical device or can be joined in an electrically conductive manner to a second cable. If the cable is connected to an electrical device, it is a cable terminal. If two cables are to be connected to one another, it is a joining device. Regardless of whether it is a terminal or a joining device, the cable or conductor is always connected by a contact element and thus, the joining device which joins two cables is also considered herein as a terminal. As such, the embodiment of the present invention is shown where the terminal connects a cable to an electrical device. However, the terminal as used herein is can be used to connect two cables as well and hence, the term terminal also refers to the joining device in the present application.

In a terminal for electrically conductive connection of a cable to an electrical device, the electrical device should be understood generally. In particular, the expression "electrical device" also includes electrical and electronic components, means and devices.

It was stated initially that the cable terminal is intended for end-face connection of the conductors of a multicore cable. First of all, it is conventional in practice for multicore cables to be connected. However, the cable terminal can also be used for those cables which have only one core.

With the initially described cable terminal or joining means generally cables are connected in which the cable insulation, but not the core insulation of the individual cores, has been removed before connection. The cable terminal or joining meansterminal, cables are

generally connected in which the cable insulation, but not the core insulation of the individual cores, has been removed before connection. The cable terminal thus enables connection of unstripped conductors. Possibilities for connecting unstripped conductors are already known from the prior art. For this purpose, so-called insulation piercing connecting devices or insulation displacement terminal ~~means~~devices are used in which the contact elements, which are generally made as contact blades, cut into the core insulation ~~from~~ laterally from outside until contact is made with the conductor. In addition, there is a second possibility for connecting unstripped conductors in which the contact elements which are generally made as contact spikes do not pierce the core insulation, but penetrate into the conductor and/or the core insulation from the end face of the cores roughly in the direction of the lengthwise axis of the cores, and make contact with the conductor.

In the cable terminal ~~or joining means~~ to be formed with ~~this invention~~the present invention, the second possibility is used, i.e. the core insulation is not cut from the side, but the conductors are connected from the end face. In doing so, ~~generally in this connection~~in this connection, stranded conductors are ~~used in which thus~~generally used. Thus, the contact element penetrates between the individual strands of the conductor. As a result of the restoration force of the core insulation, there is a clamping force sufficient for making electrical contact between the individual strands of the conductor and the contact element which has penetrated into the conductor.

German patent 44 18 259 discloses a cable terminal ~~or joining means~~ of the type under consideration; in which the core holding and guiding part consists of a plug-side gland and a cable-side end part. In the installed state of the cable ~~terminal or joining means~~terminal, the gland is pushed into a corresponding recess in the plug part. The alignment of the individual conductors to the contact elements takes place by there being four axially parallel channels for holding the cores in the core holding and guiding part and they are flush with the contact elements in the installed state. Here, the inside diameter of the channels is slightly less than

the outside diameter of the cores, by which on the one hand, clamping of the cores takes place, and on the other, via the corresponding alignment of the gland to the contact elements, the cores are also aligned to the contact elements. In addition, the cable-side end part of the core holding and guiding part is made elastic by the lengthwise slots located in the end part, by which clamping of the individual cores can be achieved for forces acting accordingly radially on the end part.

In the above described known cable ~~terminal or joining means~~terminal, exact alignment of the individual cores to the contact elements is dependent on the production tolerances of the gland of the core holding and guiding part to the corresponding recess of the plug part. In addition, for different cables with different diameters of the cores, different core holding and guiding parts are necessary. If a cable which is used has cores with smaller diameters than the core guidance channels, the alignment of the cores to the contact elements is inadequate.

German utility model 298 17 679 likewise discloses a cable ~~terminal or joining means~~ of the type under consideration, but which enables connection of different cables with different core cross sections. To do this, the core holding and guiding part consists of a rubber elastic material with axially parallel channels located in it. By squeezing the rubber elastic material together in the radial direction, the channel cross section is matched to the actual cross section of the inserted cores. But here, the disadvantage is that by squeezing together the rubber elastic material of the core holding and guiding part, not only is the channel cross section changed, but also the alignment of the channel middle to the contact elements are changed. Thus, insertion of cores with different diameters into the core guidance channels of the core holding and guiding part is indeed possible, but the accuracy of alignment of the inserted cores to the contact elements likewise, depends on the core cross sections used, so that exact alignment cannot always be ensured. In addition, the alignment

of the cores is adversely affected by aging and settling phenomena of the rubber elastic core holding and guiding part.

Summary of the Invention

~~Thus the~~ Thus, one primary object of this present invention is to make available a cable terminal ~~or joining means~~ for end-face connection of the conductors of a multicore cable in which alignment of the individual cores ~~as exact as possible~~ to the contact elements of the plug part is ~~accomplished~~ accomplished as precisely as possible. In addition, within certain limits, different cables with different core cross sections ~~are to~~ may be connected with the same cable terminal ~~or joining means~~.

The aforementioned object is first of all achieved ~~essentially~~ in that the core holding and guiding ~~means consists of~~ part includes a first section of soft material and a second section of hard material ~~and that in the first section the~~ material. The core guidance channels in the first section, and a positioning aid in the second section ~~a positioning aid~~ are formed for exact alignment of the conductors to the contact ~~elements; elements~~. The "soft material" means ~~one~~ material which is relatively elastic, whereas "hard material" means ~~one which~~ has material having little elasticity.

The embodiment of the core holding and guiding ~~means as claimed in the~~ part in accordance with the present invention enables ~~first of all~~ connection of different cables with different core cross sections. By the arrangement of the core guidance channels in the first section of the core holding and guiding part which consists of soft material, especially of a soft plastic, ~~for example~~ plastic such as a thermoplastic elastomer, the cross section of the core guidance channels can be reduced to the smaller cross section of the cores by radial pressure on this first section. In doing so, as a result of the elastic properties of the first section, sufficient clamping of the individual cores into the core guidance channels can be achieved so that the cores are prevented from slipping back when the contact elements penetrate into the

cores. ~~The~~ Moreover, the radial pressure on the first section ~~moreover~~ provides for the contact force necessary for making electrical contact between the individual strands of a conductor and the contact element which has been pushed into the conductor from the end face. Thus, the force acting radially on the core insulation ~~has~~ additionally supports the restoration force of the core insulation. Because the alignment of the cores or the conductors to the contact elements is accomplished by a positioning aid ~~which is~~ formed in the second section of the core holding and guiding part, exact alignment of the conductors to the contact elements is not influenced by the core guidance channels being pressed together. Because the second section consists of a hard plastic, ~~especially of plastic such as~~ a hard thermoplastic or of a ceramic material or other hard insulating material, the positioning aid is much less sensitive to aging and settling phenomena.

The thermoplastic elastomers for the first section can ~~be for example~~ be, for example, a natural rubber or a silicone rubber, and the first section can be produced by vulcanization.

According to one especially preferred embodiment of the invention, the first section is made in one piece from thermoplastic elastomer and the second section is made in one piece from thermoplastic. Here, the core holding and guiding part can be produced in a two-component injection molding process so that the two sections are connected to one another materially. The advantage of this core holding and guiding part which is made as a composite injected part is that in this way, it is easily ensured that the first section and the second section cannot slide or turn relative to one another.

According to one preferred ~~embodiment of~~ embodiment, the positioning aid, ~~it has~~ holes assigned to the individual core guidance channels, the holes, as viewed from the core guidance channels, having a tapering cross section. The holes can be made ~~especially~~ funnel-shaped or cone-shaped. By this configuration of the positioning aid, solely by pushing the cores through the core guidance channels into the tapering holes, "self-alignment" of the inserted cores is accomplished. ~~Exact,~~ Substantially exact, permanent alignment of the center

lines of the cores, regardless of their ~~diameter, is always~~ diameter within a range, is accomplished by the funnel-shaped or cone-shaped execution of the holes. If the contact elements of the plug part are arranged such that they are centered to the holes of the positioning aid, it is ~~always~~ ensured that the contact elements also meet the end face of the cores to be connected in the center.

The arrangement and alignment of the contact elements ~~exactly~~ centered to the holes of the positioning aid can advantageously be accomplished especially easily by the holes of the first tapering area which adjoins the core guidance channels having a second area of constant diameter and a third, widening area. The positioning aid is then used not only to align the cores, but at the same time, also to align the contact ~~elements,~~ elements so that exact alignment of the cores to the contact elements ~~being~~ is accomplished by the hole overall and thus, all three areas having a coincident center line.

It was stated above that the holes have a first tapering area, a second area of constant diameter, and a third widening area. Here, the first and the third area are made mirror-symmetrical to one another and even border one another so that the middle second area is more or less omitted or only has a negligible length. The minimum diameter of the first tapering area must always be less than the smallest diameter of the core to be connected so that the first area of the hole always forms a stop for a core which has been pushed through a core guidance channel. Conversely, the smallest diameter of the third area must always be greater than the diameter of the contact elements so that the contact elements project through the holes into the area of the core guidance channels. Ideally, the smallest diameter of the third area corresponds exactly to the outside diameter of the contact elements.

In the cable terminal ~~or joining means as claimed in the invention the embodiment~~ of in accordance with the present invention, the core holding and guiding part described in particular above is essential to the invention. The subject matter of this invention is thus not only the cable terminal ~~or joining means~~, but also the core holding and guiding part for use in

a cable terminal ~~or joining means~~. For the specific embodiment of the cable terminal ~~or joining means~~, especially of the plug part and cable receiver, there are various possibilities. What is functionally important is simply that the plug part and/or the cable receiver are made such that on the one hand, the plug part and the cable receiver can be connected to one another, and that on the other hand, radial forces are applied especially to the first section of the core holding and guiding part which consists of a soft, elastic material.

According to one advantageous embodiment of the cable terminal or joining means as claimed in the invention, there is a polarization element which acts between the plug part and the cable receiver. For this purpose for example the second section has a groove and the plug part has an assigned spring. Of course, the groove can also be assigned to the plug part and the spring to the second section or the polarization element can be made differently. This polarization element ensures polarized connection of a cable to the contact elements of the plug part.

According to one advantageous embodiment of the cable terminal ~~or joining means as claimed in the invention~~ in accordance with the present invention, the cable receiver has a sleeve with an outside thread and the plug part has a ~~coupling ring~~ union nut with an inside thread which corresponds to the outside thread of the sleeve. Thus, to assemble the cable terminal ~~or joining means as claimed in the invention~~, the cable receiver and the plug part can be easily screwed together, the core holding and guiding part being located between the cable receiver and the plug part.

The radial force on the core holding and guiding part can be easily produced by the plug part's having a sleeve part which is located within the ~~coupling ring~~ union nut, the sleeve part in the installed state surrounding the core holding and guiding part and the inside diameter of the sleeve part being at least partially smaller than the outside diameter of the core holding and guiding part. A radial force can thus, be applied to the first section of the core holding and guiding part by the arrangement of this sleeve part in the plug part, ~~by part in~~

which the core guidance channels are squeezed together and the cores which have been inserted into the core guidance channels are secured. Especially advantageous clamping of the cores in the core guidance channels in the vicinity of the positioning aid is achieved by the inside diameter of the sleeve part widening in the direction to the core holding and guiding part, ~~in part~~. In other words, the sleeve part has the smallest diameter on the side facing away from the cable receiver.

In particular, there are a host of possibilities for embodying and developing the above described cable terminal ~~or joining means as claimed in the invention~~. In this regard reference is made on the one hand to the claims subordinate to claim 1, on the other hand to the following description of one preferred embodiment in accordance with the present invention. These and other advantages and features of the present invention will become more apparent from the following detailed description of the preferred embodiments of the conjunction with the drawings.

~~Figure 1 shows a perspective view of a cable terminal or joining means as claimed in the invention in the opened state,~~

~~Figure 2 shows a view of the cable terminal or joining means corresponding to Figure 1 in the contact making state,~~

~~Figure 3 shows a schematic sketch of the core holding and guiding part of a cable terminal or joining means as claimed in the invention in cross section and~~

~~Figure 4 shows the core holding and guiding part of a cable terminal or joining means as claimed in the invention with the inserted cores having made contact with the contact elements.~~

~~Figures 1 and 2 show one embodiment of a cable terminal or joining means 1 as claimed in the invention for end face connection of the conductors of a multicore cable 3 which are shown in Figures 3, and 4, which cable has a total of five cores 4. The cable terminal or joining means 1 as claimed in the invention 1 enables connection of unstripped~~

~~conductors 2 by the contact elements 5 penetrating into the conductor 2 from the end face of the conductor 2 roughly in the direction of the lengthwise axis of the conductor 2. In doing so generally stranded conductors 2 are used in which thus the contact element 5 penetrates between the individual strands of the conductor 2. As a result of the restoration force of the core insulations 6 which surround the individual conductors 2 there is a clamping force sufficient to make electrical contact between the individual strands of the conductor 2 and the contact element 5 which has penetrated the conductor 2.~~

~~— The cable terminal or joining means 1 consists essentially of a plug part 7 in which the contact elements 5 are located, a core holding and guiding part 8 and a cable receiver 9. To connect a cable 3 to the cable terminal or joining means 1 the individual cores 4 are pushed into the core guidance channels 10 which are provided in the core holding and guiding part 8. In the embodiment shown in Figures 1 and 2 there are a total of five core guidance channels 10 which are parallel to one another in the core holding and guiding part 8 so that the cable terminal or joining means 1 shown there for electrical connection of the cables 3 is provided~~present invention when viewed in conjunction with the accompanying drawings.

Brief Description of the Drawings

Figure 1 shows a partial cross-sectional perspective view of a cable terminal in accordance with the present invention in an opened, unassembled state;

Figure 1a shows a partial cross-sectional perspective view of a cable terminal in accordance with another embodiment of the present invention in an opened, unassembled state;

Figure 2 shows a perspective view of the cable terminal corresponding to Figure 1 in the contact-making, partially assembled state;

Figure 3 shows a schematic cross-sectional view of the core holding and guiding part of the cable terminal in accordance with the present invention; and

Figure 4 shows the core holding and guiding part of a cable terminal in accordance with the present invention with the inserted cores having made contact with the contact elements.

Detailed Description of the Invention

Initially, reference is made to the definitions provided previously. In addition, as also noted above, the term "cable terminal" as used herein refer to both terminals which connect a cable to an electrical device as well as to joining devices that connect two cables together.

Figures 1 and 2 show one embodiment of a cable terminal 1 in accordance with the present invention for end-face connection of the conductors of a multicore cable 3 which are more clearly shown in Figures 3 and 4, the multicore cable having a total of five cores 4. The cable terminal 1 enables connection of unstripped conductors 2 shown in Figures 3 and 4 by the contact elements 5 penetrating into the conductor 2 from the end face of the conductor 2 roughly in the direction of the lengthwise axis of the conductor 2 in the manner shown in Figure 4. In doing so, generally stranded conductors 2 are used so that the contact element 5 penetrates between the individual strands of the conductor 2. As a result of the restoration force of the core insulation 6 which surround the individual conductors 2, there is a clamping force sufficient to make electrical contact between the individual strands of the conductor 2 and the contact element 5 which has penetrated the conductor 2.

As seen from the various figures, the cable terminal 1 of the illustrated embodiment includes a plug part 7 in which the contact elements 5 are located, a core holding and guiding part 8, and a cable receiver 9. To connect a cable 3 to the cable terminal 1, the individual cores 4 are pushed into the core guidance channels 10 which are provided in the core holding and guiding part 8. In the embodiment shown in Figures 1 and 2, there are a total of five core

guidance channels 10 in the core holding and guiding part 8 which are parallel to one another so that for the cable terminal 1 shown, there is provided with a maximum five cores 4 for electrical with a maximum five cores 4 connection of the cable 3. There are also five contact elements 5 in the plug part 7 corresponding to the five core guidance channels 10 which are present.

Figure 1a shows a partial cross-sectional perspective view of the cable terminal 1 shown in Figure 1 but with an optional polarization element which acts between the plug part 7 and the cable receiver 9 to ensure proper orientation of these components relative to one another so that the proper connection between the contact elements 5 and the conductors can be established. In the illustrated embodiment, the polarization element includes a groove 24 provided on the cable receiver 9 and a corresponding engaging mechanism such as a key or a spring (not shown) in the plug part 7 that engages the groove 24 to properly orient the plug part 7 and the cable receiver 9. Of course, in other embodiments, the groove may be provided on the plug part 7 and the corresponding engaging mechanism may be provided on the cable receiver 9 instead.

Figures 3 and 4 show a schematic of the core holding and guiding part 8 which as claimed in the invention consists of in accordance with the present invention includes a first section 11 of soft material, especially of material such as a thermoplastic elastomer, and a second section 12 of a hard material, especially material such as a hard thermoplastic or ceramic. In the first section 11, there are the core guidance channels 10, while the second section 12 of the core holding and guiding part 8 forms the positioning aid 13 for exact alignment of the conductors 2 to the contact elements 5. The core holding and guiding part 8 is preferably produced in a two-component injection molding process so that the core holding and guiding part 8 is in one piece, and the first section 11 is materially connected to the second section 12.

Figure 3 shows that the diameter of the core guidance channels 10 is greater than the diameter of the cores 4 to be connected. Here, the diameter of the core guidance channels 10 is chosen such that it corresponds to the largest diameter of the cores 4 intended for connection to the cable terminal or joining means 1. Because there are core guidance channels 10 in the first section 11 of the core holding and guiding part 8 ~~consisting of~~ made of a soft material, the core guidance channels 10 can be pressed together by applying a radial force to the first section 11 of the core holding and guiding part 8 to such an extent that sufficient axial fixing of the individual cores 4 in the core guidance channels 10 is achieved.

The positioning aid 13 of the core holding and guiding part 8 has holes 14 assigned to the core guidance channels 10, the holes 14 ~~consisting of~~ having a first tapering area 15 which adjoins the core guidance channels 10, a second area 16 of constant cross section ~~and a third section, and a third~~ widening area 17. The first tapering funnel-shaped area 15 of the hole 14 is used for exact positioning of a core 4 which has been pushed through the core guidance channel 10. Because the first area 15 of the hole 16 tapers in a funnel shape, "self alignment" of the inserted cores 4 and ~~thus also of~~ thus, also the conductors 2 with which contact is to be made always takes place so that the center line of an inserted conductor 2 always ~~agrees~~ aligns with the center line of the hole 14.

While Figure 3 shows the core holding and guiding part 8 with the cores 4 inserted, but without the contact elements 5, Figure 4 also shows the contact elements 5 inserted from the opposite direction. In the same way as the areas 15 of the holes 14 cause exact alignment of the cores 4, the conical areas 17 of the holes 14 cause exact alignment of the contact elements 5. If the outside diameter of the contact elements 5 corresponds to the smallest diameter of the hole 14, i.e. the diameter of the middle area 16, a contact element 5 which has been pushed through the hole 14 of the positioning aid 13 always meets ~~a core 4 which has been inserted into~~ the core 4 which has been inserted the core guidance channel 10 exactly in the center and thus also the conductor 2 surrounded by the core insulation 6 exactly in the

center. The embodiment of the positioning aid 13 described in detail above and the material connection of the first section 11 which has the core guidance channels 10 and the second section 12 of the core holding and guiding part 8 which has the positioning aid 13 ensures that the contact elements 5 always meet the end face of the conductors 2 in the center. In this way then optimum electrical contact between the conductors 2 and the contact elements 5 is ensured.

— One preferred possibility for assembly of the cable terminal or joining means 1 as claimed in the invention is shown in Figures 1 and 2. In the embodiment shown the cable receiver 9 and the plug part 7 can be screwed to one another by the cable receiver 9 having a sleeve 18 with an outside thread 19 and the plug part 7 having a coupling ring 20 with an inside thread 21 which corresponds to the outside thread 19 of the sleeve 18. In the assembled state of the cable terminal or joining means 1 then the core holding and guiding part 8 is surrounded by the sleeve 18 and the coupling ring 20.

— The plug part 17 has an inside sleeve 22 and a contact carrier 23 which holds the contact elements 5. The inside sleeve 22 which surrounds the core holding and guiding part 8 in the contact making state by form fit has an inside diameter which is at least partially smaller than the outside diameter of the core holding and guiding part 8. The inside contour of the inner sleeve 22 is now chosen such that in the installed state of the cable terminal or joining means 1 the first section 11 of the core holding and guiding part 8 is pressed together by the inside sleeve 22 so that the cores 4 which have been pushed into the core guidance channels 10 are clamped tight. In the embodiment of the cable terminal or joining means 1 as claimed in the invention shown which is shown in Figures 1 and 2 the cable receiver 9 has a clamp cage 24 which acts as strain relief for the inserted cable 3.

— In addition to the implementation especially of the plug part 7 and the cable receiver 9 shown in Figures 1 and 2, in which the sleeve 18 is assigned to the cable receiver 9 and the coupling ring 20 to the plug part 7, a version is also possible in which the coupling ring is

assigned to the cable receiver and the plug part has a sleeve with an outside thread. Likewise there can be a sleeve part which applies a radial force to the core holding and guiding part instead of in the plug part in the cable receiver into the core guidance channel 10 exactly in the center and thus, meets the conductor 2 which is surrounded by the insulation 6 exactly in the center. The embodiment of the positioning aid 13 described in detail above, and the material connection of the first section 11 which has the core guidance channels 10 and the second section 12 of the core holding and guiding part 8 which has the positioning aid 13, ensures that the contact elements 5 always meet the end face of the conductors 2 in the center. In this way then, optimum electrical contact between the conductors 2 and the contact elements 5 is ensured.

One embodiment for assembly of the cable terminal 1 in accordance with the present invention is shown in Figures 1 and 2. In the embodiment shown, the cable receiver 9 and the plug part 7 can be screwed to one another via the cable receiver 9 having a sleeve 18 with an outside thread 19, and the plug part 7 having a union nut 20 with an inside thread 21 which corresponds to the outside thread 19 of the sleeve 18. In the assembled state of the cable terminal 1 then, the core holding and guiding part 8 is surrounded by the sleeve 18 and the union nut 20.

The plug part 17 of the illustrated embodiment has an inside sleeve 22 and a contact carrier 23 which holds the contact elements 5. The inside sleeve 22 which form-fittingly surrounds the core holding and guiding part 8 when in the contact-making state, has an inside diameter which is at least partially smaller than the outside diameter of the core holding and guiding part 8. The inside contour of the inner sleeve 22 is preferably chosen such that in the installed state of the cable terminal 1, the first section 11 of the core holding and guiding part 8 is pressed together by the inside sleeve 22 so that the cores 4 which have been pushed into the core guidance channels 10 are clamped tight. In the embodiment of the cable terminal 1

shown in Figures 1 and 2, the cable receiver 9 has a clamp cage 24 which acts as strain relief for the inserted cable 3.

In addition to the embodied implementation of the plug part 7 and the cable receiver 9 shown in Figures 1 and 2 in which the sleeve 18 is assigned to the cable receiver 9 and the union nut 20 to the plug part 7, an embodiment is also possible in which the union nut is assigned to the cable receiver and the plug part has a sleeve with an outside thread. Likewise, in other embodiments, there can be a sleeve part in the cable receiver which applies a radial force to the core holding and guiding part instead of in the plug part.

While various embodiments in accordance with the present invention have been shown and described, it is understood that the invention is not limited thereto. The present invention may be changed, modified and further applied by those skilled in the art. Therefore, this invention is not limited to the detail shown and described previously, but also includes all such changes and modifications.